

## Check sound levels according to the regulations

- Designed according to IEC 651 type 2 standard
- 3 measurement ranges
- 2 integration times / 2 weighting curves

<b>Measurement range</b>	3 measurement ranges 37 dB to 130 dB
<b>Accuracy</b>	± 1.5 dB
<b>Resolution</b>	0.1 dB
<b>Integration time</b>	slow (550 ms)
	fast (55 ms)
<b>Weighting curves</b>	dB(A) and dB(C)
<b>Analogue output</b>	10 mV/dB and 1 Vrms on 600 Ω

- ✓ Hold function
- ✓ Backlighting
- ✓ 2000-count display
- ✓ Tripod mounting
- ✓ **C.A 833** Calibrator: source adjusted to 94 dB and 114 dB for calibrating your sound level meter

#### Operating conditions:

- Temperature: 0 to 50 °C
- Humidity: < 80 % RH

#### Storing conditions:

- Temperature: -20 °C to +60 °C
- Humidity: < 80 % RH

#### Dimensions:

- 205 x 60.5 x 38 mm

#### Mass:

- 230 g

To order	
<b>C.A 832</b> Sound Level Meter	P01.1855.01Z
<b>C.A 833</b> Calibrator	P01.1853.01

## Sound Level Meter

